


SK170 LIFTING CAPACITIES



Lifting Capacities in Accordance with F.E.M. standards

JIB MODEL	L1	L2	L3	L4	L5
MAX HOOK REACH	91'-3"	117'-5"	149'-0"	170'-0"	191'-0"
HOOK REACH	LIFTING CAPACITIES IN POUNDS, TWO PART LINE				
11'-2"	22,000	22,000	22,000	22,000	22,000
51'-10"	22,000	22,000	22,000	22,000	22,000
54'-0"	22,000	22,000	22,000	22,000	21,000
56'-0"	22,000	22,000	22,000	22,000	20,200
58'-0"	22,000	22,000	22,000	22,000	19,300
60'-4"	22,000	22,000	22,000	22,000	18,300
61'-4"	22,000	22,000	22,000	21,500	18,000
63'-8"	22,000	22,000	21,000	20,600	17,300
65'-4"	22,000	21,400	20,500	20,000	16,700
70'-0"	20,300	19,700	18,900	18,500	15,500
75'-0"	18,800	18,300	17,400	17,000	14,300
80'-0"	17,500	17,000	16,200	15,800	13,200
85'-0"	16,300	15,700	15,000	14,700	12,300
90'-0"	15,100	14,800	14,000	13,700	11,500
91'-3"	15,000	14,500	13,700	13,400	11,200
95'-0"		13,800	13,100	12,800	10,800
100'-0"		13,000	12,400	12,000	10,100
110'-0"		11,500	11,000	10,700	9,000
117'-5"		10,800	10,000	9,800	8,200
130'-0"			8,900	8,700	7,200
140'-0"			8,200	8,000	6,500
149'-0"			7,700	7,300	6,000
160'-0"				6,700	5,300
170'-0"				6,400	5,000
180'-0"					4,600
191'-0"					4,400