


SK180 LIFTING CAPACITIES



Lifting Capacities in Accordance with F.E.M. standards

JIB MODEL	L1	L2	L3	L4	L5
MAX HOOK REACH	101'-0"	134'-6"	168'-0"	184'-9"	196'-0"
HOOK REACH	LIFTING CAPACITIES IN POUNDS, TWO PART LINE				
9'-2"	13,800	13,800	13,800	13,800	13,800
81'-0"	13,800	13,800	13,800	13,800	13,800
90'-0"	13,800	13,800	13,800	13,800	12,300
95'-0"	13,800	13,800	13,800	13,800	11,700
101'-0"	13,800	13,800	13,800	12,900	10,800
106'-0"		13,800	13,800	12,300	10,200
110'-0"		13,800	13,300	11,800	9,700
120'-0"		12,600	12,100	10,700	8,700
130'-0"		11,500	11,000	9,700	8,000
134'-6"		11,000	10,600	9,300	7,700
140'-0"			10,100	8,800	7,300
150'-0"			9,300	8,200	6,700
160'-0"			8,600	7,600	6,200
168'-0"			8,200	7,200	5,800
180'-0"				6,600	5,400
184'-9"				6,400	5,200
190'-0"					5,100
196'-0"					4,900