


SK400 LIFTING CAPACITIES



Lifting Capacities in Accordance with F.E.M. standards

JIB MODEL	L1	L2	L3	L4	L5	L6
MAX HOOK REACH	123'-6"	161'-6"	180'-6"	199'-6"	218'-6"	244'-6"
HOOK REACH	LIFTING CAPACITIES IN POUNDS, TWO PART LINE					
9'-10"	22,000	22,000	22,000	22,000	22,000	22,000
88'-0"	22,000	22,000	22,000	22,000	22,000	22,000
100'-0"	22,000	22,000	22,000	22,000	22,000	19,200
112'-6"	22,000	22,000	22,000	22,000	22,000	16,700
120'-0"	22,000	22,000	22,000	22,000	20,400	15,500
123'-6"	22,000	22,000	22,000	22,000	19,700	15,000
126'-0"		22,000	22,000	22,000	19,300	14,700
134'-0"		22,000	22,000	20,500	18,000	13,700
139'-0"		22,000	21,000	19,700	17,200	13,100
150'-0"		20,100	19,200	18,100	15,800	12,000
161'-6"		18,500	17,700	16,600	14,500	11,000
170'-0"			16,700	15,600	13,600	10,400
180'-6"			15,700	14,600	12,700	9,500
190'-0"				13,700	12,000	9,000
199'-6"				13,000	11,500	8,400
210'-0"					10,600	7,900
218'-6"					10,100	7,500
230'-0"						7,000
240'-0"						6,700
244'-6"						6,600